

















## Detektori dima, toplote, gasa, vode...


















MAGELLAN





	<p><b>Optički detektor dima</b>                      Auto Reset, Otporan na insekte i prašinu                      Pokriva obast od 80m2 (kada je instaliran na visini od 6 do 12m) odnosno 60m2 (kada je instaliran na visini manjoj od 6), radna temperatura -10°C do 50°C, 12VDC                      Dimenzije: 104x51 mm</p>	<p><b>BS-M532</b></p>	
	<p><b>Optički detektor dima, stand alone</b>                      Visoka osetljivost i brzi odgovor, EN1 4604 standard. Ugradjena sirena 85dB                      Radna temperatura -10°C do 80°C, 9 V                      Dimenzije: 110x25 mm</p>	<p><b>BS-M547</b></p>	
	<p><b>Detektor zemnog gasa, nije stand alone</b>                      Montira se na zid, visoka osetljivost, automatski reset (nakon alarma). Napajanje : 12VDC/24VDC/220VAC, ugrađena sirena 85dB, radna temperatura a 0°C do 55°C, alarmna koncentracija 10% LEL±3%LEL, N.C./N.O.                      Dimenzije: 110x70x38 mm</p>	<p><b>BS-GD610</b></p>	
	<p><b>Ugljen monoksid gasni detektor (CO), stand alone</b>                      Visoka pouzdanost, zvučna i vizuelna signalizacija alarma. Napajanje 9 V, sirena jačine 85dB, alarmna koncentracija 150±50ppm, radna temperatura a 0°C do 55°C</p>	<p><b>BS-COD935</b></p>	
	<p><b>Ugljen monoksid gasni detektor (CO) nije standalone</b>                      Visoka pouzdanost, zvučna i vizuelna signalizacija alarma. Auto reset, sirena jačine 85dB, alarmna koncentracija 150±50ppm, radna temperatura a 0°C do 55°C, 12 VDC</p>	<p><b>BS-COD934</b></p>	
	<p><b>Detektor vode nije standalone</b>                      12 VDC, N.C./N.O.                      Dimeniyje 60x25x90 mm</p>	<p><b>BS-WD100</b></p>	
Magnetni kontakti			
	<p><b>Magnetni kontakt, bela boja, zaliven, sa kablovima</b></p>	<p><b>MS 13S</b></p>	
	<p><b>Metalni magnetni kontakt, metalno rebrasto crevo</b></p>	<p><b>MS 42M</b></p>	
	<p><b>Magnetni kontakt, bela boja, plastični, ugradni</b>                      Dimenzije <math>\phi</math>10x31 mm</p>	<p><b>BS-MC105R/FC503</b></p>	

## Panik tasteri, tasteri, pedale, brave

	<b>Panik taster - plastični</b>	<b>BS EB02</b>	
		1,98    2,38	
	<b>Panik taster sa ključem</b>	<b>BS EB01</b>	
		2,28    2,74	
	<b>Nagazna panik podloga</b> Dimenzije 102.5 x 67 x 28 mm, NO/NC kontakt, u crnoj boji	<b>BS-PS103</b>	
		4,14    4,97	
	<b>Metalni ugradni taster</b> za otvaranje vrata, široki	<b>PB 86MT</b>	
		6,47    7,76	
	<b>Plastični taster</b> Dimenzije: 86x86x17	<b>BS-EB02A</b>	
		3,17    3,80	
	<b>Metalni nadgradni taster</b> za otvaranje vrata, uski	<b>GM-EB13</b>	
		9,40    11,28	
	<b>Metalni taster, ugradni</b>	<b>RB-800A</b>	
		7,82    9,38	
<b>Infracrvene barijere</b>			
	<b>IC barijera, 10m</b> , 2 snopa, visina 408 mm imunost na životinje do 25 kg, vreme odziva 40ms, radna temperatura -25°C do +55°C, ugao podesivosti ±90°	<b>BS-IF-2/10m</b>	
		26,96    32,35	
	<b>IC barijera, 30m</b> , 2 snopa, visina 408 mm imunost na životinje do 25 kg, vreme odziva 40ms, radna temperatura -25°C do +55°C, ugao podesivosti ±90°	<b>BS-IF-2/30m</b>	
		30,96    37,15	
	<b>IC barijera, 20m</b> , 4 snopa, visina 708 mm imunost na životinje do 25 kg, vreme odziva 40ms, radna temperatura -25°C do +55°C, ugao podesivosti ±90°	<b>BS-IF-4/20m</b>	
		38,82    46,58	
	<b>IC barijera, 40m</b> , 4 snopa, visina 708 mm imunost na životinje do 25 kg, vreme odziva 40ms, radna temperatura -25°C do +55°C, ugao podesivosti ±90°	<b>BS-IF-4/40m</b>	
		45,21    54,25	
	<b>IC barijera, 40m</b> , 8 snopa, visina 1628 mm imunost na životinje do 25 kg, vreme odziva 40ms, radna temperatura -25°C do +55°C, ugao podesivosti ±90°	<b>BS-IF-8/40m</b>	
		71,01    85,21	
	<b>IC barijera, 50m</b> , 8 snopa, visina 1628 mm imunost na životinje do 25 kg, vreme odziva 40ms, radna temperatura -25°C do +55°C, ugao podesivosti ±90°	<b>BS-IF-8/50m</b>	
		78,85    94,62	

	<b>IC barijera, 10m/20m</b> , 1 snop radna temperatura -25°C do +55°C	<b>BS-BD1</b>		14,51	17,41
	<b>IC barijera, 20m/60m</b> , 2 snopa radna temperatura -25°C do +55°C, ugao podesivosti ±10°, ±90°C, IP65, težina 500g, dimenzije 80mmx80mmx170mm	<b>BS-BD2/20</b>		24,87	29,84
	<b>IC barijera, 40m/120m</b> , 2 snopa radna temperatura -25°C do +55°C, ugao podesivosti ±10°, ±90°C, IP65, težina 500g, dimenzije 80mmx80mmx170mm	<b>BS-BD2/40</b>		26,90	32,28
	<b>IC barijera, 60m/180m</b> , 2 snopa radna temperatura -25°C do +55°C, ugao podesivosti ±10°, ±90°C, IP65, težina 500g, dimenzije 80mmx80mmx170mm	<b>BS-BD2/60</b>		28,93	34,72
	<b>IC barijera, 100m/300m</b> , 2 snopa radna temperatura -25°C do +55°C, ugao podesivosti ±10°, ±90°C, IP65, težina 500g, dimenzije 80mmx80mmx170mm	<b>BS-BD2/100</b>		32,48	38,98
	<b>IC barijera, 60m/120m</b> , 2 snopa Radni napon 10,8~25VDC, potrošnja 57mA, mogućnost podešavanja brzine reagovanja 50msec ~ 700msec, temperaturni opseg rada -20&deg;C ~ 60&deg;C, IP43	<b>PB-60</b>		79,07	94,88
<b>Univerzalne daljinske komande</b>					
AP050305 	Univerzalna daljinska komanda, 2 kanala set sadrži centralu i 1 daljinac	<b>UR 1</b>		27,91	33,49
	<b>Daljinski upravljač sa slajderom za UR 1</b> 2 tastera	<b>RC 1</b>		6,60	7,92
	<b>Univerzalna daljinska komanda, 4 kanala,</b> set sadrži centralu i 2 daljinca	<b>UR 2</b>		29,94	35,93
	<b>Daljinski upravljač sa slajderom za UR 2</b> 4 tastera	<b>RC 2</b>		6,60	7,92
<b>Sirene i bliceri</b>					

	<b>Spoljna sirena sa blicerom</b> , antisabotažno zaštićena, dvostruko zaštićena, 128dB, pozitivna i negativna trigeracija, alarm u slučaju gubitka napajanja, zaštita od kratkog spoja, trepćuće svetlo levo i desno, automatsko testiranje svih parametara uz indikaciju nepravnosti, tajmer, indikacija praznog akumulatora	<b>BS-OS359</b>		31,72	38,06
	<b>Spoljna sirena sa blicerom</b> , antisabotažno zaštićena, dvostruko zaštićena, 115±3 dB pozitivna i negativna trigeracija, alarm u slučaju gubitka napajanja, zaštita od kratkog spoja, indikacija praznog akumulatora	<b>BS-OS357</b>		23,47	28,16
	<b>Spoljna sirena sa blicerom</b> , 115±3 dB alarm u slučaju gubitka napajanja,	<b>BS-OS361</b>		26,00	31,20
	<b>Spoljasnja sirena</b> , 105Db, crveno svetlo, tamper	<b>SL 300</b>		11,17	13,40
	<b>Unutrašnja sirena sa strob svetlom</b> , piezo 108dB	<b>BS-PS352</b>		4,75	5,70
<b>Napajanja</b>					
	Olovni hermetički zatvoreni akumulator 12V/7Ah	<b>UL7-12</b>		14,90	17,88
	Olovni hermetički zatvoreni akumulator 12V/1.3Ah	<b>UL1.3-12</b>		8,10	9,72
	Olovni hermetički zatvoreni akumulator 12V/2.4Ah UL2.4	<b>UL2.4-12</b>		9,88	11,86
<b>Ostala oprema</b>					
	<b>Transformator 30VA</b>	<b>Trafo 30VA</b>		10,86	13,03

	<b>Transformator 40VA</b>	<b>Trafo 40VA</b>	
		13,12	15,74
	<b>Transformator 30VA, zaliveni sa osiguračem</b>	<b>Trafo Z</b>	
		12,37	14,84
	<b>Tamper</b>	<b>BS-ATS-1</b>	
		1,10	1,32